


1. DIMENSION ARE IN INCHES
2. DIMENSIONS ARE FOR REFERENCE ONLY
3. BUBBLE CALLOUTS REFER TO BILL OF MATERIALS
4. P/N 040-9108-XXX WHERE XXX IS LENGTH IN FEET
LENGTH TOLERANCE FOR CABLE: -3%, +5%
(NOT TO EXCEED 2 FEET)
5. THIS ASSEMBLY MUST BE ROHS COMPLIANT

	DENOTES CONNECTOR PIN 1 ORIENTATION WITH RESPECT TO CABLE STRAIN RELIEF
	DETAIL A: MODULAR PLUG SIDE VIEW
	REFER TO STANDARD OPERATING PROCEDURE
	REFER TO SHIPPING LABEL P/N 131244, ITEM 4, "ROHS COMPLIANT" PACKAGING IDENTIFICATION

DS1 TEST PATCH CORD, 2 SINGLE BANTAM PLUGS TO 1 RJ48 PLUG




DDJ	MOD	
TIP-----WHT---PIN 1 RING----BLK-----PIN 2		CORD 1
TIP-----WHT----PIN 4 RING----BLK-----PIN 5		CORD 2

A5	ECO MX2833C, REMOVE CHINA ROHS	02 JUL 2013	JJC	JJC
REV	DESCRIPTION	DATEBY FOR		

APPROVALS		DATE
DRAWN BY	C. VERDAL	23 APR 2002
DESIGNED BY	N. CONANT	25 AUG 1997
APPROVED BY		
ORIGINAL DRAWING DATE		25 AUG 1997

NOT FOR REPRODUCTION COPYRIGHT 2013

This document contains proprietary information that is property of TELECT, INC., Spokane, Washington. It is intended for the exclusive use of our customer for information, installation, and/or service. The recipient agrees not to reproduce or copy this document or its contents in whole or in part without prior written permission from TELECT, INC. This document must be returned promptly if no longer needed or upon written request from TELECT, INC.

		1730 N. Madison Street / P.O. Box 665 Liberty Lake, Washington 99019 (509) 926-6000 www.telect.com	
TITLE PATCH CORD: 2 PAIR, STRANDED, SHIELDED, 2 SINGLE BANTAMS TO RJ48 MOD PLUG PC:TP,2 SGL BNTM/RJ48,ROHS			
DWG TYPE C	PART NO. 040-9108-XXX		DWG SIZE B
PROJECT VISIO DWG			ISSUE A
SCALE NTS		SHEET 1 OF 1	REV 5